

[54] **DRY WALL JOINT AND FINISHING COMPOUNDS**

[75] Inventor: **William F. Brown**, Wausau, Wis.

[73] Assignee: **Weston Research, Corporation**, Rothschild, Wis.

[21] Appl. No.: **954,445**

[22] Filed: **Oct. 25, 1978**

[51] Int. Cl.³ **C04B 11/14**

[52] U.S. Cl. **106/116; 260/29.6 S**

[58] Field of Search **106/111, 116; 260/29.6 S, 29.6 PS**

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|-----------|--------|----------------|------------|
| 3,256,223 | 6/1966 | Heijmer | 260/29.6 S |
| 3,947,398 | 3/1976 | Williams | 260/29.6 S |

Primary Examiner—James Poer
Attorney, Agent, or Firm—Michael, Best & Friedrich

[57] **ABSTRACT**

The dry wall joint compound, which can be used to completely close and fill joints between adjoining panel of gypsum dry wall board without a tape material, comprises a powdered mixture of gypsum, hydrated gypsum, calcium carbonate, plaster of paris, hydrated amorphous silica and talc. The dry wall joint compound can be admixed with water to provide a dry wall joint cement and preferably is admixed with a liquid additive composition comprising an aqueous mixture of zinc oxide, sodium acetate, ammonium alum, and an acrylic resin.

6 Claims, No Drawings